



QUICK COMPARISON OF UPVC SERIES

4 THERMAL INSERTS

STANDARD

OPTIONS

FEATURES:			SYSTEMS				
							
			* DPQ-82 thermoSecure	* DPQ-82	DPQ-76	DPP-70	
PROFILE							
NUMBER OF CHAMBERS IN FRAME				7	7	5	5
Optimal number of chambers provides better thermal insulation							
PVC PROFILE THICKNESS				82 mm	82 mm	76 mm	70 mm
Greater profile thickness allows to increase the number of the chambers allowing for better insulated frames.							
PERIMETER-SEALS				3	3	3	2
Greater amount of seals improves window tightness							
CONSTRUCTION REINFORCEMENT				full steel in frame	full steel in frame	full steel in frame	full steel in frame
Reinforcement of PVC profile provides increased stability and protection.							
HANDLE							
HANDLE TYPE				Secustik	standard, made of aluminium	standard, made of aluminium	standard, made of aluminium
Solid handles available in a range of styles and colors							
STANDARD GLASS PACKET							
TYPE OF GLASS PACKET				3-glass packet, 4x18x4x18x4 with Chroma-tech warm-edge spacer	3-glass packet 4x18x4x18x4	3-glass packet 4x14x4x14x4	3-glass packet 4x14x4x14x4
Greater the number of chambers in glass packet provides better thermal insulation							
U VALUE - GLASS & FRAME *				.13 - Fixed .14 - operable	.14 - Fixed .16 - operable	.16 - Fixed .17 - operable	.16 - Fixed ** .18 - operable
Lower U value number, the better the thermal insulation							
SPACE BETWEEN GLASS				✓	✓	✓	✓
Filled with Argon gas . Krypton gas available							
STANDARD HARDWARE							
STANDARD HARDWARE				Standard Plus	Standard	Standard	Standard
Commercial grade hardware, long-lasting and secure.							
OPTIONAL HARDWARE OPERATIONS							
SLOT VENTILATION				✓	✓	✓	✓
INVISIBLE HINGES				✓	✓	✓	✓
TILT FIRST				✓	✓	✓	✓
CHOSEN ENERGY EFFICIENT SPECIAL GLASSES							
3-glass packet 4/14/4/14/4	(U _g = 0,6 W/m ² K)		✓	✓	✓	✓	✓
Increased thermal insulation							
3-glass packet 44.4/14/4/14/4	(U _g = 0,6 W/m ² K)		✓	✓	✗	✗	✗
Security and protection							
3-glass packet 4/14/4/14/33.1	(U _g = 0,6 W/m ² K)		✓	✓	✗	✗	✗
Warmth and security							
3-glass packet 44.2/12/6/12/6	(U _g = 0,7 W/m ² K)		✓	✓	✗	✗	✗
Silence and security							
4-glass packet 4/12/4/12/4/12/4	(U _g = 0,3 W/m ² K)		✓	✓	✗	✗	✗
Maximum energy saving							

✓ - standard ✗ - unavailable

* U values converted from EU testing divided by 5.678

** DPP-70 is NFRC tested

* DPQ-82 Series available with exterior aluminum cladding in custom colors

413.774.9946

www.scenicwindowcompany.com

info@scenicwindowcompany.com


QUICK COMPARISON OF wood SERIES

PROFILE

SYSTEM




DDA 78 **



DDF-92 AL



DDF-78 AL



DDF-68 AL

PROFILE

PROFILE THICKNESS

Greater profile thickness provides better thermal insulation



78 mm

92 mm

78 mm

68 mm

PERIMETER-SEALS

Higher number of seals improves window tightness



3

3

3

3

HANDLE

HANDLE TYPE

Solid handles available in a range of styles and colors



standard, made of aluminium

standard, made of aluminium

standard, made of aluminium

standard, made of aluminium

STANDARD GLASS PACKET

GLASS PACKET

Higher number of chambers in the glazing unit provides better thermal insulation



3-glass panes,
4x14x4x14x4

3-glass panes
4x16x4x16x4

3-glass panes
4x14x4x14x4

2-glass packet
4x16x4

U VALUE - GLASS & FRAME *

Lower U value number, the better the insulation



.15 - Fixed
.16 - operable

.13 - Fixed
.14 - operable

.15 - Fixed
.16 - operable

.25 - Fixed
.26 - operable

SPACE BETWEEN GLASS

Filled with Argon gas . Krypton gas available



✓

✓

✓

✓

STANDARD HARDWARE

STANDARD HARDWARE

Commercial grade hardware, long-lasting and secure.



Standard

Standard

Standard

Standard

CHOSEN SPECIAL FITTINGS

TILT FIRST



●

●

●

●

INVISIBLE HINGES



●

●

●

●

CHOSEN ENERGY EFFICIENT SPECIAL GLASSES

3-glass packet 4/18/4/18/4

Warmth and extra lighting

(U_g = 0,6 W/m²K)



×

●

×

×

3-glass packet 44.4/14/4/14/4

Security and protection

(U_g = 0,6 W/m²K)



×

●

×

×

3-glass packet 4/14/4/14/33.1

Warmth and security

(U_g = 0,6 W/m²K)



●

●

●

×

3-glass packet 44.2/12/6/12/6

Silence and security

(U_g = 0,7 W/m²K)



●

●

●

×

4-glass packet 4/12/4/12/4/12/4

Maximum energy saving

(U_g = 0,3 W/m²K)



×

●

×

×

✓ - standard ● - optional ✕ - unavailable

* U values converted from EU testing divided by 5.678

** DDA78 profile available in 9 exterior styles

www.scenicwindowcompany.com

info@scenicwindowcompany.com

STANDARD

OPTIONS

